

# TwistPort™ Adaptor for ePMP-A

INTEGRATES EPMP CONNECTORIZED RADIOS INTO TWISTPORT™ ECO-SYSTEM

The TwistPort™ Adaptor for ePMP™ 1000 AP and CSM, ePMP™ 3000L AP and ePMP™ Force 300 CSM series, PMP 450b is compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick-locking waveguide connector with near zero loss.

Connecting and disconnecting the radio into the TwistPort™ Adaptor is very simple and requires no tools.



## TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h (100 mi/h)
Weight	0.4 Kg / 0.9 lbs – single unit 11.2 Kg / 24.7 lbs – carton (20 units)
Single Unit	Retail Box: 130 x 120 x 135 mm (5.1 x 4.7 x 5.3 inch)
20 Units	Carton Box: 295 x 280 x 610 mm (11.6 x 11 x 24 inch)

## PERFORMANCE

Frequency Range	See antenna datasheet for frequency range
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

## COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Cambium Networks™	ePMP™ 1000 AP, ePMP™ 1000 CSM, ePMP™ 3000L AP, ePMP™ Force 300 CSM, PMP 450b, PMP 450 MicroPoP

## PACKAGE CONTENTS

TwistPort™ Adaptor

## PRODUCT DIMENSIONS

