

Product:

EAV-Bridge

Mechanical

Dimensions	109 x 134.4 x 40.4 mm (4.3 x 5.3 x 1.6")
Weight	560 g (1.2 lb)
Enclosure Material	Aluminum
Mounting	DIN rail, Wall, Pole (Included)
Pole Mount Diameter	1.5–2" (38–50 mm)

Audio

Output	Mono / Stereo sound
Surround Format	PCM
Audio Input	(1) HDMI in (2) XLR female analog with 6.35 mm analog combo input, phantom power: 48V DC supported
Audio Output	(1) HDMI out (2) XLR male analog output
Frequency	20 Hz – 20k Hz $\pm$ 0.5dB

Video

Video Input	(1) HDMI 2.0, 4K at 60 Hz (60 FPS)
Video Output	(1) HDMI 2.0, 4K at 60 Hz (60 FPS)
Video Content Support	480p / 720p / 1080p / 4K
Signal Distribution	1-to-1, 1-to-N streaming 1 to 8x8 TV wall configuration

Hardware

Networking Interface	(1) GbE RJ45 PoE+ In Etherlighting™ port
Versatile Port	(1) USB Type-C 5V, 1A
IR Connection	(1) 3.5 mm Input or Output
Power Method	PoE+
Max. Power Consumption	14W
LCM Display	(1) 1.3" touchscreen
Button	(1) Factory reset
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	5 to 90% noncondensing
NDAA Compliant	✓
Certifications	FCC, IC, CE
Etherlighting™	
Ethernet	✓





