

# Enterprise Fortress Gateway

EFG

## Mechanical

Dimensions	442.4 x 43.7 x 325 mm (17.4 x 1.7 x 12.8")
Weight	6.5 kg (14.3 lb)
Enclosure material	Aluminium CNC, SGCC steel

## Hardware

Processor	18-core ARM® v8.2 at 2 GHz
System memory	16 GB DDR4 DIMM
Management interface	EthernetBluetooth
Networking interface	(2) 25G SFP28 ports(2) 10G SFP+ ports(2) 2.5 GbE RJ45 portsMap any (2) interfaces to WAN
Power method	(1) Universal AC input, 100—240V AC, 7A Max., 50/60 Hz
Power supply	(2) Hot-swappable 150W CRPS
Supported voltage range	100—240V AC
Max. power consumption	82W
ESD/EMP protection	Air: ± 8kV, contact: ± 4kV
LCM display	(1) 1.3" touchscreen
Button	Factory reset
Ambient operating temperature	0 to 40° C (22 to 104° F)
Ambient operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

## Gateway Features

Performance	Redundant WAN with failover and load balancing WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Additional internet failover with LTE Backup Internet quality and outage reporting
Next-generation security	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation Full stateful firewall
Advanced networking	License-free SD-WAN WireGuard, L2TP and OpenVPN server OpenVPN client OpenVPN and IPsec site-to-site VPN One-click Teleport and Identity VPN Policy-based WAN and VPN routing DHCP relay Customizable DHCP server IGMP proxy IPv6 ISP support

## Capacity

UniFi devices	500+
Client devices	5,000+
Concurrent sessions	1 million
New sessions / sec	71,000
SSL/TLS inspection concurrent sessions	10,000 Limiting to 5,000 concurrent sessions is recommended if the gateway is passing significant traffic. This can be achieved by restricting which VLANs and domains pass through NeXT AI Inspection, such as only including search engine and LLM queries on employee devices. <a href="#">Learn more.</a>
IDS/IPS signatures	80,000+ With Enhanced Threat Updates. <a href="#">Learn more.</a>

## Routing Throughput

Firewall	23.5 Gbps
IDS/IPS	12.5 Gbps

## VPN Server Single User Throughput

UniFi Identity	1.2 Gbps
Teleport	1.2 Gbps
WireGuard	1.2 Gbps
OpenVPN	210 Mbps
L2TP	280 Mbps

---

## Site-to-Site VPN Single Tunnel Throughput

Site Magic	1.1 Gbps
OpenVPN	120 Mbps
IPsec	580 Mbps

---

## VPN Client Single Tunnel Throughput

WireGuard	980 Mbps
OpenVPN	180 Mbps

---

## LEDs

Ethernet	White: Link/activity
SFP+	White: Link/activity
CRPS	Off: No AC power present Steady white: AC power and DC output active Flashing white: AC power present Steady red: AC power lost/failure events Flashing red: Warning events

---

## Software

Mobile app	UniFi iOS™: Version 10.16.2 and later UniFi Android™: Version 10.17.2 and later
------------	--

