

Product:

ENVR

Overview

Dimensions	481.4 x 480 x 132 mm (19 x 18.9 x 5.2")
Managed Cameras	(210) HD (140) 2K (70) 4K
Storage Capacity	(16) 3.5" drive bays
Data Protection	✓
Vantage Point	✓
Networking Interface	(2) 10G SFP+ (1) 10 GbE
Power Redundancy	✓
Form Factor	Rack Mount (3U)
Door Access Support	✓
UniFi Application Suite	
Protect	✓
Access	✓

Hardware

Hard Drive Capacity	(16) 2.5/3.5" HDD / SSD support
Max. Power Budget for Drives	310W
Max. Power Consumption	410W
Power Method	(2) AC input, 100-240V, 7A Max., 50/60Hz (Redundant, hot-swappable)
Power Supply	Hot-swappable 550W CRPS

Processor	MV-CN10208-A0-CF240AA-C250-SCP
Memory	32 GB
Management	Ethernet
Display	Bezel (Optional)
Weight	Without rails: 16.6 kg (36.6 lb) With rails: 19.5 kg (43.0 lb)
Enclosure Material	SGCC steel
Mount Material	Aluminum
Slide Rails	482.6 mm (19") four-post racks Posts depths ranging from 650 to 1,000 mm (25.6–39.4")
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC
NDAA Compliant	✓



Datasheet



