

Product:

UACC-Adapter-PoE-24-12W

Overview

Dimensions	89 x 46 x 33 mm (3.5 x 1.8 x 1.3")
Weight	100 g (3.5 oz)
Power Cable	Included
Input Voltage Range	100–240V AC
Input Frequency	50/60Hz
Output Voltage	24V
Rated Voltage	24V
Connector	C6
Networking Interface	RJ45
Gigabit LAN Port	✓
Remote Reset Capability	✓
Reset Button	✓
2-pair Powering	Pins 4, 5 (+) and Pins 3, 6, 7, 8 (-)
AC Connector	IEC-320 C6
Output Current	0.5A
Data In / PoE	RJ45 shielded socket
Input Current	0.3A @ 120V AC 0.2A @ 240V AC
Inrush Current	<30A peak @ 120V AC <60A peak @ 230V AC
Efficiency	82.96%
Switching Frequency	50 kHz

Output Ripple	1% Max.
Line Regulation	≤ 3%
Load Regulation	≤ 5%
Max. Surge Discharge	1500A (8/20 μs) power
Peak Pulse Current	36A (10/1000 μs) data
Max. Power Consumption	0.1W
Response Time	<1 ns
Shunt Capacitance	<5 pF data
Supported Voltage Range	22.8–25.2V
Total Output Power	12W
Over Current Protection	0.6–1A
Surge Protection	Difference and Common mode
ESD/EMP Protection	6KV/10KV
Ambient Storage Temperature	-30 to 70° C (-22 to 158° F)
Ambient Operating Temperature	0 to 40° C (32 to 104° F)
Ambient Operating Humidity	5 to 95%, noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, UL,PSE, BSMI