

Product: UACC-Rack-12U-Wall-450-G

Overview

Dimensions	Packaging: 580 x 675 x 735 mm (22.8 x 26.6 x 28.9") Rack: 550 x 450 x 635 mm (21.7 x 17.7 x 25")
Weight	Packaging: 23.2 kg (51.1 lb) Rack: 19 kg (41.9 lb)
Enclosure Material	SPCC steel Door/side panels: 0.8 mm (0.03") Main body: 0.8 mm (0.03") Posts: 2 mm (0.08")
Color	White
Treatment	Powder coating
Supported Devices	Compatible with Ubiquiti rack-mount devices up to 325 mm in depth. Note: 325 mm devices can be installed when the mounting depth is set to 305 mm (max), but DC power backup is not supported due to limited rear-side clearance.
NDAA Compliant	✓

Rack Features

U Height	12U
Rack Type	4 post, enclosed cabinet
Mounting Hole Type	Square
Adjustable Mounting Depth	Default 283 mm (11.1") Max. 305 mm (12") Adjustable pitch 22 mm (0.9")
Max. Weight Capacity	50 kg (110 lb)
Front Door	Tempered glass Default left-hand outswing, reversible
Side Panels	(2) Solid, removable and lockable
Mounting	Wall mount
Fan Module	(2) Pre-installed 120 x 120 x 38 mm AC fan units
Acoustic Noise	≤ 50 dB(A) sound pressure level
Grounding Lugs	✓
Cable Entry Opening	(1) Rear wall: 350 x 100 mm (13.8 x 3.9") (1) Top: 336.5 x 52.5 mm (13.2 x 2.1") (1) Bottom: 336.5 x 52.5 mm (13.2 x 2.1")
Security	(1) Front door lock (4) Side panel locks (2) Keys
Standard	CE; EIA/ECA-310-E; RoHS





