

Product:

UC-EV-Station-Lite

Overview

Dimensions	254.7 x 192.7 x 85 mm (10 x 7.6 x 3.3")
Mounting	Wall Mount or Stand
Power Input	200–240V ~ 50A, 50/60Hz, 1φ
Power Output	200–240V ~ 50A, 50/60Hz, 1φ
Weatherproofing	Type 3R

Mechanical

Weight	5.9 kg (13 lb)
Enclosure Material	Polycarbonate
Charging Cable Length	7 m (23 ft)

Hardware

Processor	Dual-core Arm® Cortex®-A53, 1 GHz
Connectivity	(1) GbE RJ45 port (1) USB-C port Bluetooth® 5.0 WiFi
Ambient Operating Humidity	5 to 90% noncondensing
Ambient Operating Temperature	-40 to 50° C (-40 to 122° F)
NDAA Compliant	✓
Certifications	FCC, IC, UL



Display

Size

1.7" status display

Circuit Rating

Max. load

70A: 50A

60A: 48A

50A: 40A

40A: 32A

30A: 24A

20A: 16A

Plug-in

70A: No

60A: No

50A: Yes

40A: Yes

30A: Yes

20A: Yes

Hardwired

70A: Yes

60A: Yes

50A: Yes

40A: Yes

30A: Yes

20A: Yes

Software

Management Application

UniFi Connect: Version 3.14.4 and later.

UniFi Connect iOS™ and Android™: Version 2.18 and later.



Datasheet



