

Fiber OLT XGS

UISP-FIBER-OLT-XGS

Mechanical

Dimensions	442.4 x 285.6 x 43.7 mm (17.4 x 11.2 x 1.7")
Weight	5.29 kg (11.7 lb)
Enclosure material	SGCC steel

Hardware

Networking interface	(8) XGS/XG/GPON ports(4) 1/10/25G SFP28 ports**The four SFP28 ports don't support mixed speed at 25 Gbps mode. Once one of the SFP28 ports is configured at 25 Gbps mode, the others will be limited at 25 Gbps too. The SFP28 ports only support mixed speed when all ports are at 1 Gbps or 10 Gbps.
Management interface	Ethernet out-of-bandEthernet in-bandRJ45 serial console portBluetooth
Memory	512 MB DDR3
Onboard flash storage	64 MB NOR + 512 MB NAND
Power method	(1) Universal AC input, 100-240V AC, 50/60 Hz
Power supply	(2) Hotswap AC/DC PSU
Supported voltage range	100–240V AC
Max. power consumption	70W
Button	(1) Factory reset
Ambient operating temperature	-10 to 45° C (14 to 113° F)
Ambient operating humidity	10 to 95% non-condensing
Certifications	CE, FCC, IC

LEDs

System

Slow blinking white: system is booting
 Fast blinking white: reset to default
 Blinking white/blue: system is upgrading
 Slow blinking blue: system is connecting to UISP
 Fast blinking blue: locate system
 Steady white: system is ready
 Steady blue: system is ready and connected to UISP

MGMT port

(1) White, steady on after link is up

PON ports

(8) Steady white: PON link

SFP28 ports

(4) White, steady on after link is up

