



## Product:

## UP-AI-Port

### Overview

|                      |                                                                                                           |
|----------------------|-----------------------------------------------------------------------------------------------------------|
| Dimensions           | Without mount: 150 x 64 x 38.4 mm (5.9 x 2.5 x 1.5")<br>With mount: 152.7 x 69 x 47.8 mm (6 x 2.7 x 1.9") |
| Resolution           | Max. camera resolution:<br>Width: 3840 pixels<br>Height: 2160 pixels                                      |
| Networking Interface | (1) GbE RJ45 port                                                                                         |

### Hardware

|                               |                                                                                                    |
|-------------------------------|----------------------------------------------------------------------------------------------------|
| Power Method                  | PoE<br>PoE+ input required for PoE output (12.95W)<br>PoE++ input required for PoE+ output (25.5W) |
| Pole Mount Diameter           | >45 mm (1.8") on pipe outer diameter                                                               |
| Weight                        | Without mount: 258.3 g (9.1 oz)<br>With mount: 294 g (10.4 oz)                                     |
| Enclosure Material            | Polycarbonate                                                                                      |
| Button                        | Factory-reset                                                                                      |
| Ambient Operating Temperature | -20 to 40° C (-4 to 104° F)                                                                        |
| Ambient Operating Humidity    | 20 to 90% noncondensing                                                                            |
| NDAA Compliant                | ✓                                                                                                  |
| Certifications                | FCC, IC, CE                                                                                        |

### Software

## Application Requirements

Web Application

UniFi Protect: Version 5.1 and later

Mobile App

UniFi Protect iOS™ and Android™



\*PoE+ input required for PoE output (12.95W), PoE++ input required for PoE+ output (25.5W).

\*\*Rack mount sold separately.

\*\*\* SD card support coming soon.

