

Product:

USL-FOB

Overview

Dimensions	67 x 35 x 18.5 mm (2.6 x 1.4 x 0.7")
UniFi Application Suite	Protect

Performance

Connectivity	SuperLink (Proprietary)
Operating Frequency	
US	915.6–927.6 MHz
EU	865.1–869.5 MHz
Max. TX Power	
SuperLink	14 dBm
Max. Range	
SuperLink	2 km (1.2 mi)

Hardware

Max. Power Consumption	150mW
Supported Voltage Range	3V
Power Method	(1) Lithium battery CR2450
Battery Life	Up to 10 years
Weight	32 g (1.1 oz)
Enclosure Material	Polycarbonate
Buttons	(4) Top buttons: Primary faceplate: Arm, Disarm, Night mode, Panic Secondary faceplate: Numeric (1, 2, 3, 4) for programmable functions



(2) Side buttons for programmable functions

LEDs

(1) Status: R/B/W

(1) Signal: B/R

Ambient Operating Temperature

0 to 40° C (32 to 104° F)

Ambient Operating Humidity

10 to 90% noncondensing

Certifications

CE, FCC, IC, UL 4200A

NDAA Compliant



Battery Info

Size

24.5 x 5 mm (1 x 0.2")

Nominal Voltage

3V

Nominal Capacity

600 mAh

Max. Pulse Current

50 mA

Software

Application Requirements

Web Application

UniFi Protect

Mobile App

UniFi Protect iOS™ and Android™





