

Product:

USW-Pro-XG-24

Overview

Dimensions	442 x 480 x 44 mm (17.4 x 18.9 x 1.7")
Redundancy	DC Power Backup
Layer 3	✓
Form Factor	Rack mount (1U)
Etherlighting™	✓
Port Layout	
2.5 GbE RJ45	8 (2.5G/1G/100M/10M)
10 GbE RJ45	16 (10G/5G/2.5G/1G/100M/10M)
25G SFP28	2 (25G/10G/1G)

Performance

Switching Capacity	460 Gbps
Total Non-Blocking Throughput	230 Gbps
Forwarding Rate	342 Mpps
Supported VLANs	1,000
MAC Address Table Size	128,000
Packet Buffer Size	8 MB

L3 Table Size

ARP Entries	128,000
IPv4 Routes	256,000

Access Lists

IPv4	256
MAC	256

Layer 3 Features

DHCP Server (Local Networks)	✓
DHCP Relay	✓
Inter-VLAN Routing (Local Networks)	✓
Static Routing (Local Networks)	✓

Layer 2 Features

LACP Port Aggregation	✓
STP & RSTP	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓

MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓

Hardware

Max. Power Consumption	150W
Power Method	(1) Universal input, 100–240V AC, 50/60 Hz (1) USP RPS DC input
Power Input Method	AC input
Power Supply	AC/DC, internal, 200W
Supported Voltage Range	100–240V AC
Management	Ethernet AR
Weight	Without mounting brackets: 7.2 kg (15.9 lb) With mounting brackets: 7.3 kg (16.1 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	482.6 mm (19") four-post racks

Posts depths ranging from 600 to 1,066 mm (23.6-42")

LCM Display	1.3" touchscreen
ESD/EMP Protection	Air: $\pm 30\text{kV}$, contact: $\pm 20\text{kV}$
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDA A Compliant	✓
Certifications	CE, FCC, IC
Etherlighting™	
Ethernet	✓
SFP28	✓
LEDs	
RPS	✓

Software

Application Requirements

UniFi Network	Version 9.0.114 and later
---------------	---------------------------



Datasheet

1.3" touchscreen
with AR switch management

(8) Multi-speed 2.5 GbE ports
(2.5G/1G/100M/10M)

(16) Multi-speed 10 GbE ports
(10G/5G/2.5G/1G/100M/10M)



(2) 25G SFP28
ports

Reset
button

DC power backup*

Layer 3 switching features



Power input

Safety latch

*Require UniFi Power Backup.

(24) Etherlighting™ RJ45 ports that illuminate to indicate port location, speed/link, and native VLAN/network**



**Pair with UniFi Etherlighting Patch Cables for optimal brightness.

