

Mechanical

Dimensions	141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")
Weight	520 g (1.1 lb)
Enclosure material	Polycarbonate
Resistance	IK04

Hardware

Processor	Quad-core ARM® Cortex®-A53 at 1.5 GHz
Memory information	2 GB DDR4
Management interface	EthernetBluetooth
Networking interface	LAN:(4) 2.5 GbE RJ45 portsWAN:(1) 2.5 GbE RJ45 port
IDS/IPS throughput	1.5 Gbps**Measured with iPerf3 on DHCP WAN. Performance may be reduced with PPPoE depending on ISP implementation.
Power method	USB type C (5V/3A)
Supported voltage range	100–240V
Max. power consumption	9.6W
LED	EthernetWhite: link/activity
Button	(1) Factory reset
Ambient operating temperature	-10 to 40° C (14 to 104° F)
Ambient operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC


Gateway Features

Performance	WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Internet quality and outage reporting
Next-generation security	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation Full stateful firewall
Advanced networking	License-free SD-WAN* WireGuard, L2TP and OpenVPN server OpenVPN client OpenVPN and IPsec site-to-site VPN One-click Teleport* and Identity Enterprise VPN** Policy-based WAN and VPN routing DHCP relay Customizable DHCP server IPv6 ISP support* When paired with a CloudKey or Official UniFi Hosting. **When paired with a CloudKey.

Application Requirements

UniFi Network

Version 8.1.113 and later



*5V DC, 3A USB-C adapter included.