



20TB¹
7200 RPM | SATA 6Gb/s and SAS 12Gb/s

Product Highlights

- 20TB capacity in a standard 3.5-inch form factor
- ePMR & CMR technology works with all capacity enterprise applications & environments
- OptiNAND for highest capacities
- Reliable, field-proven, 7th generation HelioSeal design delivers outstanding power efficiency
- Industry-leading HDD technologies; OptiNAND, EAMR, TSA, HelioSeal
- 2.5M hours (projected) MTBF rating & 5-year limited warranty
- Self-Encrypting Drive (SED) options

Applications

- Cloud and hyperscale storage
- Massive scale-out (MSO), high-density data centers
- Distributed file systems
- Bulk storage using object storage solutions like Ceph™ and OpenStack® Swift
- Primary and secondary storage for Apache Hadoop® for big data analytics

Features and Benefits

Features	Benefits
High capacity Industry-first technologies	20TB HDDs allow more cost-efficient storage in the same footprint. OptiNAND, energy-assisted magnetic recording (EAMR), triple-stage actuator (TSA) and HelioSeal enable the highest capacities with low power.
Data center workloads, reliability, and quality	Performance-optimized for heavy application workloads and are designed to handle workloads up to 550TB ² per year. Dependability and reliability with up to 2.5M hours MTBF (projected). 5-year limited warranty.

Reimagining the HDD for Exponential Data Growth

Hyperscale cloud, CSPs, enterprises, smart video surveillance partners, NAS suppliers and more, need storage solutions to meet the exponential growth in data creation. When it comes to cost-effective storage of data at scale, hard disk drives (HDDs) continue to play a central role. IDC projects that in 2025, HDDs will represent 82% of storage capacity sold to the enterprise market*. HDDs deliver the capacity, performance, and reliability needed to store vast amounts of data today and well into the future. Investments in HDD technology remain critical to supporting worldwide data growth.

Western Digital has developed flash-enhanced drives with OptiNAND™ technology by vertically integrating the company's leading NAND flash with its world-class HDDs. Western Digital HDDs have been leaders in areal density with industry first technologies of energy-assisted magnetic recording technology (EAMR), triple-stage actuator (TSA), HelioSeal®, and now OptiNAND technology. Higher areal density means higher capacities to meet storage challenges.

20TB HDDs with OptiNAND Technology

OptiNAND integrates an iNAND® Universal Flash Storage (UFS) Embedded Flash Drive (EFD) with traditional spinning disk media, and incorporates innovative changes to the firmware algorithm and system-on-a-chip (SoC). OptiNAND is not a hybrid technology. The drive works smarter, with enhanced firmware algorithms taking advantage of expanded metadata that has been offloaded to the iNAND, enabling more tracks per inch (TPI), resulting in increased areal density.

The Ultrastar DC HC560, with the first implementation of OptiNAND technology's capacity-enabling features, delivers an unbeaten 20TB capacity in a nine-disk platform (2.2TB/platter) with CMR recording format.

Trusted Reliability and Quality for Data at Scale

The Ultrastar DC HC560 meets modern data center reliability requirements with 2.5M MTBF (projected) and a 5-year limited warranty. It offers security and encryption options to help protect data from unauthorized use, including SED models.

Trust Western Digital and the Ultrastar DC HC560 hard drive to deliver the highest capacity and greatest value for your data center.

* IDC Worldwide Hard Disk Drive Forecast Update, 2021-2025 – Doc #US47633120; and IDC Worldwide Solid State Drive Forecast Update, 2021-2025, May 2021, Doc #US46412021

Specifications

	SATA Models	SAS Models
Model Numbers	WUH722020ALE6L1 WUH722020ALE6L4 WUH722020BLE6L1 WUH722020BLE6L4	WUH722020BL5201 WUH722020BL5204
Part Numbers	0F38754 (SED) 0F38755 (Base SE) 0F38784 (SED) 0F38785 (Base SE)	0F38651 (SED) 0F38652 (Base SE)
Configuration		
Interface	SATA 6Gb/s	SAS 12Gb/s
Capacity ¹	20TB	20TB
Format: Sector size (bytes) ²	4Kn: 4096, 512e: 512	4Kn: 4096, 512e: 512
Areal Density (Gbits/sq. in, max)	1131	1131
Performance		
Data buffer ³ (MB)	512	512
Rotational speed (RPM)	7200	7200
Latency average (ms)	4.16	4.16
Interface transfer rate (MB/s, max)	600	1200
Sustained transfer rate ⁴ (MB/s, max) / (MiB/s, max)	291/277	291/277
Random Read ⁴ 4KB QD=32 (IOPS)	212	212
Random Write ⁴ 4KB QD=32, WCE/WCD (IOPS)	494/455 [*] 565/565 ^{**}	565/565
Reliability		
Error rate (non-recoverable bits read)	1 in 10 ¹⁵	1 in 10 ¹⁵
Load/Unload cycles (at 40°C)	600,000	600,000
Availability (hrs/day x days/wk)	24x7	24x7
MTBF ⁵ (M hours, projected)	2.5	2.5
Annualized Failure Rate ⁵ (AFR, projected)	0.35%	0.35%
Workloads	Up to 550 TB/year	Up to 550 TB/year
Limited warranty (yrs)	5	5

¹ One MB is equal to one million bytes, one GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes). Actual user capacity may be less due to operating environment.

² Advanced Format drive: 4K (4096-byte) physical sectors.

³ Portion of buffer capacity used for drive firmware

⁴ Based on internal testing; performance may vary depending on host environment, drive capacity, logical block address (LBA), and other factors. The location of the max rate is at approximately 10% into the capacity of the HDD. 1MiB = 1,048,576 bytes (2²⁰), 1MB = 1,000,000 bytes (10⁶)

⁵ Projected values. Final MTBF and AFR specifications will be based on a sample population and are estimated by statistical

measurements and acceleration algorithms under typical operating conditions, typical workload and 40°C device-reported temperature. Derating of MTBF and AFR will occur above these parameters, up to 550TB/year and 60°C (device reported temperature). MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

⁶ SATA models:
Random RW 50/50 8KB QD=1 @40 IOPS,
SAS models:
Random RW 50/50 4KB QD=4 @MAX IOPS

⁷ Idle specification is based on use of Idle_A.

⁸ 5°C ambient temperature, 60°C device reported temperature.

	SATA Models	SAS Models
Acoustics		
Idle/Operating (Bels, typical)	2.0/3.2	2.0 / 3.2
Power		
Requirement	+5 VDC, +12VDC	+5 VDC, +12VDC
Operating ⁶ (W)	7.0 [*] 6.9 ^{**}	9.3
Idle ⁷ (W)	6.1 [*] 5.8 ^{**}	6.1
Power consumption efficiency at idle (W/TB)	0.305 [*] 0.29 ^{**}	0.305

Physical Size		
z-height (mm)	26.1	26.1
Dimensions (width x depth, mm)	101.6 (+/-0.25) x 147	101.6 (+/-0.25) x 147
Weight (g, max)	690	690

Environmental (Operating)		
Temperature ⁸	5° to 60°C	5° to 60°C
Shock (half-sine wave, 2ms, G)	50	50
Vibration (G RMS, 5 to 500Hz)	0.7 (XYZ)	0.7 (XYZ)

Environmental (Non-operating)		
Ambient temperature	-40° to 70°C	-40° to 70°C
Shock (half-sine wave, 2ms, G)	250	250
Vibration (G RMS, 2 to 200Hz)	1.04 (XYZ)	1.04 (XYZ)

^{*} For model/part numbers WUH722020ALE6L1/0F38754, WUH722020ALE6L4/0F38755
^{**} For model/part numbers WUH722020BLE6L1/0F38784, WUH722020BLE6L4/0F38785

How to Read the Ultrastar Model Number

WUH722020ALxxyz

W = Western Digital
U = Ultrastar
H = Helium (vs. S for Standard)
72 = 7200 RPM
20 = Full capacity (20TB)
20 = Capacity this model (20TB)
A = Generation code
L = 26.1 z-height

xx = Interface
E6 = 512e SATA 6Gb/s,
S2 = 512e SAS 12Gb/s
y = Power Disable Pin 3 status
0 = Power Disable Pin 3 support
L = Legacy Pin 3 config – no Power Disable support
z = Data Security Mode
1 = SED*: Self Encrypting Drive
TCG-Enterprise and Sanitize
Crypto Scramble / Erase
4 = Base (SE)*: No Encryption. Sanitize
Overwrite only.

* ATA Security Feature Set comes standard on SATA

Western Digital.

5601 Great Oaks Parkway
San Jose, CA 95119, USA
US (Toll-Free): 888.426.5214
International: 408.717.6000

www.westerndigital.com

© 2022 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital logo, HelioSeal, OptiNAND, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. Apache Hadoop is either a registered trademark or trademark of the Apache Software Foundation in the United States and/or other countries. Ceph is a trademark of Red Hat, Inc. in the U.S. and other countries. The OpenStack Word Mark is a registered trademark/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. All other marks are the property of their respective owners. References in this publication to Ultrastar products, programs or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications and do not constitute a warranty. Actual specifications for unique part numbers may vary. Pictures shown may vary from actual products.