

Specifications



Photo is representative



Eaton 5E700UD

Eaton 5E Gen2 UPS USB DIN, 700 VA, 360 W,
Input: Schuko, Outputs: (2) DIN, Tower

General specifications

| | |
|-----------------------------|--|
| PRODUCT NAME | Eaton 5E Gen2 UPS |
| CATALOG NUMBER | 5E700UD |
| EAN | 3553340704192 |
| PRODUCT LENGTH/DEPTH | 288 mm |
| PRODUCT HEIGHT | 148 mm |
| PRODUCT WIDTH | 100 mm |
| PRODUCT WEIGHT | 4.31 kg |
| WARRANTY | 2 year |
| COMPLIANCES | CB LVD Directive EMC Directive RoHS Directive Packaging Directive WEEE Directive Batteries Directive |
| CERTIFICATIONS | IEC/EN 62040-1 IEC/EN 62040-2 CE EAC Ukr IEC/EN 62040-3 UKCA Cm |



Powering Business Worldwide

Product specifications

SPECIAL FEATURES

- Automatic Voltage Regulation (AVR)
- Saves space with a compact tower design
- HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)
- Includes two Schuko (DIN) Outlets

| | |
|-----------------------------------|---|
| TOPOLOGY | Line-interactive |
| CONSTRUCTION TYPE | Free standing model |
| COLOR | Black |
| VA RATING | 700 VA |
| WATTAGE | 360 W |
| RACK MOUNTING KIT | No |
| PACKAGE CONTENTS | <ul style="list-style-type: none">• Quick start• Safety instructions |
| SURGE PROTECTION | Yes |
| INTERNAL BYPASS | No |
| HOT SWAP POWER | No |
| AUTO SHUTDOWN FUNCTION | Yes |
| PRIMARY FREQUENCY - MAX | 63 Hz |
| PRIMARY FREQUENCY - MIN | 45 Hz |
| INPUT CONNECTION | Protective contact (SCHUKO) |
| INPUT CORD LENGTH | 1.2 m |
| INPUT NOMINAL VOLTAGE | 230V default (220/230/240V) |
| NOMINAL FREQUENCY | 50/60 Hz |
| INPUT FREQUENCY RANGE | 45-63 Hz |
| RECEPTACLE | (2) Schuko |
| NUM OF OUTPUTS PC (SCHUKO) | 2 |
| VOLTAGE | 230V |
| OUTPUT NOMINAL VOLTAGE | 230V |

Resources

| | |
|-------------------------|--|
| BROCHURES | eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf |
| CERTIFICATION REPORTS | eaton-dpq-5egen2-ups-certificate-en-gb.pdf |
| MANUALS AND USER GUIDES | eaton-dpq-5egen2-ups-manual-en-gb.pdf |
| TECHNICAL DATA SHEETS | eaton-dpq-5egen2-ups-datasheet-en-gb.pdf |

| | |
|--------------------------------------|---|
| FEED TYPE | 1 |
| VOLTAGE TYPE | AC |
| RUNTIME GRAPH | View runtime graph |
| BATTERY MANAGEMENT | Automatic battery test, deep-discharge protection, cold-start capable |
| BATTERY RATING | 12 V / 7 Ah |
| BATTERY TYPE | Sealed, lead-acid |
| EXTENDED BATTERY CAPABILITY | No |
| COMMUNICATION | USB port (HID compliant) |
| EXPANSION SLOTS | No |
| ETHERNET INTERFACE | No |
| INCLUDES NETWORK CARD | No |
| SOFTWARE COMPATIBILITY | Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings) |
| USER INTERFACE | LEDs |
| TYPE OF INTERFACE | USB |
| POTENTIAL FREE SWITCH CONTACT | No |
| RELATIVE HUMIDITY | 0-90% non-condensing |
| TEMPERATURE RANGE | 0° to 40°C (32° to 104°F) |
| OPERATING TEMPERATURE - MAX | 40 °C |
| OPERATING TEMPERATURE - MIN | 0 °C |
| OUTPUT APPARENT POWER | 700 VA |
| INPUT VOLTAGE - MAX | 300 V |
| INPUT VOLTAGE - MIN | 140 V |
| OUTPUT VOLTAGE - MAX | 257 V |
| OUTPUT VOLTAGE - MIN | 195 V |
| SECONDARY FREQUENCY - MAX | 60 Hz |
| SECONDARY FREQUENCY - MIN | 50 Hz |
| BATTERY QUANTITY | 1 |
| EFFICIENCY AT MAX. LOAD | 95 |
| INPUT VOLTAGE RANGE | 140-300 V |
| OUTPUT FREQUENCY | 50/60 Hz |
| OUTPUT VOLTAGE | 195-257 V |

| | |
|-----------------------|---|
| RANGE | |
| PHASE (INPUT) | 1 |
| PHASE (OUTPUT) | 1 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

